

Version 3.0		Revision Date 04/23/2018	Print Date 07/19/2023
SECTION 1. PRODUCT AND	COMPA	ANY IDENTIFICATION	
Material name	:	A07297 ZP FOAMING COIL 02020	01_12CS 20N18
Material number	:	00000000000020201	
Manufacturer or supplie	er's deta	ils	
Company	:	Zep Inc.	
Address	:	350 Joe Frank Harris Parkway, SE Emerson, GA 30137	1

Telephone : 404-352-1680

Emergency telephone numbers

For SDS Information	:	Compliance Services 1-877-428-9937
For a Medical Emergency	:	877-541-2016 Toll Free - All Calls Recorded
For a Transportation	:	CHEMTREC: 800-424-9300 - All Calls Recorded.
Emergency		In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

Recommended use : Specialty Cleaner and Remover

Note: This product is labeled as a consumer product in accordance with the United States Consumer Product Safety Commission regulations. The warnings presented below in this Safety Data Sheet (SDS) comply with the 2012 OSHA Hazard Communication Standard (GHS - Globally Harmonized System of Classification and Labeling). The requirements for the labeling and warnings of consumer products may differ from those required for GHS based hazard communication.

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a liquefied gas		
Colour	colourless, clear		
Odour	characteristic		

GIIS Classification	
Gases under pressure Skin corrosion Serious eye damage	: Liquefied gas : Category 1 : Category 1
GHS label elements	
Hazard pictograms	
Signal word	: Danger
Hazard statements	: H280 Contains gas under pressure; may explode if heated. H314 Causes severe skin burns and eye damage.

GHS Classification



Version 3.0	Revision Date 04/23/2018	Print Date 07/19/2023
Precautionary statements	 Prevention: P260 Do not breathe dust or mist. P264 Wash skin thoroughly after I P280 Wear protective gloves/ protection/ face protection. P251 Pressurized container: Do nuse. Response: P301 + P330 + P331 IF SWALLO induce vomiting. P303 + P361 + P353 IF ON SKIN immediately all contaminated clot P304 + P340 + P310 IF INHALED and keep comfortable for breathin POISON CENTER/doctor. P305 + P351 + P338 + P310 IF IN water for several minutes. Remove and easy to do. Continue rinsing. CENTER/doctor. P363 Wash contaminated clothing Storage: P410 + P412 Protect from sunligh temperatures exceeding 50 °C/ 12 P403 Store in a well-ventilated plate Disposal: P501 Dispose of contents/contain regulation. 	handling. tective clothing/ eye not pierce or burn, even after WED: Rinse mouth. Do NOT (or hair): Take off hing. Rinse skin with water. : Remove person to fresh air g. Immediately call a N EYES: Rinse cautiously with e contact lenses, if present Immediately call a POISON g before reuse. t. Do not expose to 22 °F. ace.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

: Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
1-(1-methyl-2-propoxyethoxy)propan-2-ol	29911-27-1	>= 3 - < 5
butane	106-97-8	>= 3 - < 5
propane-1,2-diol	57-55-6	>=1-<3
propane	74-98-6	>= 1 - < 3

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

General advice	: Do not leave the victim unattended. Move out of dangerous area. Show this safety data sheet to the doctor in attendance.
lf inhaled	 If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.



Version 3.0		Revision Date 04/23/2018	Print Date 07/19/2023
In case of skin contact	:	Wash off immediately with plenty of wa minutes. If skin irritation persists, call a physicia	
In case of eye contact	:	Remove contact lenses. Rinse immediately with plenty of water Keep eye wide open while rinsing.	for at least 15 minutes.
If swallowed	:	Keep respiratory tract clear. Never give anything by mouth to an ur DO NOT induce vomiting unless direct physician or poison control center.	•
Most important symptoms and effects, both acute and delayed	:	Effects are immediate and delayed. Effects are dependent on exposure (do contact time). Symptoms may include blistering, irrita Causes severe skin burns and eye dar Review section 2 of SDS to see all pot	tion, burns, and pain. nage.
Notes to physician	:	Treat symptomatically. Symptoms ma	y be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	Carbon dioxide (CO2) Carbon monoxide Smoke
Specific extinguishing methods	:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Further information	:	Standard procedure for chemical fires.
Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions,	: Use personal protective equipment.
protective equipment and	Ensure adequate ventilation.
emergency procedures	Remove all sources of ignition.
	Beware of vapours accumulating to form explosive
	concentrations. Vapours can accumulate in low areas.
	•



Version 3.0	Revision Date 04/23/2018	Print Date 07/19/2023
Environmental precautions	: Prevent further leakage or spillag Prevent product from entering dra If the product contaminates rivers respective authorities.	ains.
Methods and materials for containment and cleaning up	: Soak up with inert absorbent mat acid binder, universal binder, saw Sweep up or vacuum up spillage container for disposal.	vdust).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	 For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Always replace cap after use. Do not breathe vapours or spray mist.
Conditions for safe storage	 BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Keep in a dry, cool and well-ventilated place. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards. No smoking.
Materials to avoid	: Do not freeze. Store and keep away from, oxidizing agents and acids.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
		PEL	800 ppm 1,900 mg/m3	CAL PEL
propane-1,2-diol	57-55-6	TWA	10 mg/m3	US WEEL



/ersion 3.0	Revision	Date 04/23/2018	Print	Date 07/19/2023
propane	74-98-6	TWA TWA	1,000 ppm 1,000 ppm	ACGIH NIOSH REL
		TWA	1,800 mg/m3 1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
		PEL	1,000 ppm 1,800 mg/m3	CAL PEL
Engineering measures	: effective	ventilation in all pr	ocessing areas	
Personal protective equip	ment			
Respiratory protection	ventilation	n is provided or ex	unless adequate loc (posure assessmen ecommended expos	t demonstrates
Hand protection Material Remarks		•	workplace should rotective gloves.	be discussed
Eye protection	: Tightly fit	: Tightly fitting safety goggles		
Skin and body protection	Choose b	Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.		
Hygiene measures		Wash hands before breaks and at the end of workday. When using do not eat, drink or smoke.		

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Aerosol containing a liquefied gas
Colour	: colourless, clear
Odour	: characteristic
Odour Threshold	: No data available
рН	: 12 - 13
Melting point/freezing point	: Not applicable
Boiling point	: 100 °C
Flash point	: Not applicable
Evaporation rate	: 1
Flammability (solid, gas)	: Not classified as a flammability hazard



Version 3.0	Revision Date 04/23/2018	Print Date 07/19/2023
Upper explosion limit	: Not applicable	
Lower explosion limit	: Not applicable	
Vapour pressure	: No data available	
Relative vapour density	: No data available	
Density	: 1.017 g/cm3	
Solubility(ies)		
Water solubility	: soluble in hot water, soluble in cold v	vater
Solubility in other solvents	: soluble	
Partition coefficient: n- octanol/water	: No data available	
Auto-ignition temperature	: not determined	
Thermal decomposition	: No data available	
Viscosity		
Viscosity, kinematic	: No data available	
Heat of combustion	: < 20 kJ/g	

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Oxidizing agents Acids
Hazardous decomposition products	: Carbon oxides Organic Substances

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical Condition	:	None known.
Symptoms of Overexposure	:	Effects are immediate and delayed. Effects are dependent on exposure (dose, concentration,



Version 3.0	Revision Date 04/23/2018	Print Date 07/19/2023
	contact time). Symptoms may include blistering,	irritation, burns, and pain.
Carcinogenicity:		
IARC	Group 2A: Probably carcinogenic to h	numans
ACGIH	sodium nitrite No component of this product present equal to 0.1% is identified as a carcin carcinogen by ACGIH.	
OSHA	No component of this product present	
NTP	equal to 0.1% is on OSHA's list of reg No component of this product present equal to 0.1% is identified as a known by NTP.	at levels greater than or
Acute toxicity		
Product:		
Acute oral toxicity	: Acute toxicity estimate : > 5,000 m Method: Calculation method	g/kg
Skin corrosion/irritation		
Product:		
Remarks: Causes skin bur	ns.	
Serious eye damage/eye irrit	ation	
Product:		
Remarks: Risk of serious	damage to eyes.	
Respiratory or skin sensitisat	ion	
No data available		
Germ cell mutagenicity		
No data available		
Carcinogenicity		
No data available		
Reproductive toxicity		
No data available		
STOT - single exposure		
No data available		
STOT - repeated exposure		
No data available		
Aspiration toxicity		
No data available		
	7 / 12	



Version 3.0

Revision Date 04/23/2018

Print Date 07/19/2023

Further information

Product:

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available **Bioaccumulative potential**

Product:

Partition coefficient: n- octanol/water <u>Components:</u>	: Remarks: No data available
1-(1-methyl-2-propoxyethoxy)p	ronan-2-ol :
Partition coefficient: n-	
octanol/water	. FOW.7.7
butane :	. Baun 0.00
	: Pow: 2.89
octanol/water	
propane-1,2-diol :	
	: log Pow: -1.07
octanol/water	
Mobility in soil	
No data available	
Other adverse effects	
No data available	
Product:	
Degulation	40 CEP Distantion of Environments Dart 92 Distantion of
Regulation	40 CFR Protection of Environment; Part 82 Protection of
	Stratospheric Ozone - CAA Section 602 Class I
	Substances
Remarks	This product neither contains, nor was manufactured
	with a Class I or Class II ODS as defined by the U.S.
	Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A
	+ B).
Additional ecological	: No data available
information	

SECTION 13. DISPOSAL CONSIDERATIONS



Version 3.0	Revision Date 04/23/2018	Print Date 07/19/2023
Disposal methods		
Waste from residues	: Do not dispose of waste into sewe Do not contaminate ponds, waterw chemical or used container. Dispose of in accordance with loca	ays or ditches with
Contaminated packaging	 Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch 	on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IATA (Cargo Air): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IATA (Passenger Air): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.

The following substance(s) is/are subject to TSCA 12(b) export notification requirements: sodium nitrite 7632-00-0

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
sodium nitrite	7632-00-0	100	*



Version 3.0	Revision Date 04/23/2018	Print Date 07/19/2023
*: Calculated RQ exceeds re	easonably attainable upper limit.	
SARA 304 Extremely Haza	ardous Substances Reportable Quantit	у
This material does not conta	ain any components with a section 304 El	HS RQ.
SARA 311/312 Hazards	: Gases under pressure Skin corrosion or irritation Serious eye damage or eye irritation	1
SARA 302	: No chemicals in this material are sul requirements of SARA Title III, Sect	
SARA 313	: This material does not contain any or known CAS numbers that exceed th reporting levels established by SAR	e threshold (De Minimis)
California Prop. 65		
	WARNING: This product can expo including toluene, which is/are known to cause birth defects or other rep	own to the State of California

information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

DSL	All components of this product are on the Canadian DSL
TSCA	On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION




Version 3.0

Revision Date 04/23/2018

Print Date 07/19/2023





HMIS III:

HEALTH	3
FLAMMABILITY	2
PHYSICAL HAZARD	3

0 = not significant, 1 =Slight,

OSHA - GHS Label Information:

Hazard pictograms	
Signal w ord	: Danger:
Hazard statements	 Contains gas under pressure; may explode if heated. Causes severe skin burns and eve damage.
Precautionary statements	:
	 Prevention: Do not breathe dust or mist. Wash skin thoroughly after handling. Wear protective gloves/protective clothing/ eye protection/ face protection. Pressurized container: Do not pierce or burn, even after use. Response: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with w ater. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. Wash contaminated clothing before reuse. Stor age: Protect fromsunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a w ell-ventilated place. Disposal: Dispose of contents/container in accordance with local regulation.

Version:	3.0
Revision Date:	04/23/2018
Print Date:	07/19/2023

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®,Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®,

^{2 =} Moderate, 3 = High 4 = Extreme, * = Chronic



Version 3.0

Revision Date 04/23/2018

Print Date 07/19/2023

Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National[™], FC Forward Chemicals®,Rexodan®, Mykal[™], and a number of private labeled brands.